



## Car / Equipment Hauler, Medium & Heavy Duty Trailers

	CH 816	CH 818	MD-816	MD-818	HD818-12K
<b>Overall Length</b>	19' 10"	21' 10"	19' 10"	21' 10"	21' 10"
<b>Overall Width</b>	101-1/2"				
<b>Bed Width</b>	82" (between fenders)				
<b>Bed Length w/ Beavertail</b>	16'	18'	16'	18'	18'
<b>Beavertail</b>	3' (diamond plate steel)			3' (wood deck)	
<b>Decking</b>	2"x10" treated pine				
<b>Bed Height</b>	22"	22"	23"	23"	23"
<b>Axles</b>	(2) Dexter E-Z Lube				
<b>Brakes</b>	Electric - both axles				
<b>Wheels</b>	5 bolt 15" (white spoke)		6 bolt 15" (silver mod)		8 BOLT 16" SILVER MOD
<b>Tires</b>	ST 205/75 D15 Load Range "C"		ST 225/75 D15 Load Range "D"		LT 245/75R16 Load Range "E"
<b>Suspension</b>	Double eye springs				
<b>Jack</b>	5000 lbs. Drop leg		7000 lbs. Drop Leg		
<b>Coupler Size</b>	2-5/16"				
<b>Ramps</b>	(2) 54"x16" rear slide-in			5' Stand Up	
<b>Winch Mount</b>	1 (standard)			-	
<b>Stake Pockets</b>	(8) 4 per side				
<b>Steps</b>	(4) 2 per side				
<b>Lighting</b>	LED standard				
<b>GVWR</b>	7000 lbs.		9,990 lbs		12,000 lbs.
<b>GAWR</b>	7000 lbs.		10,400 lbs.		12,000 lbs.
<b>Trailer Weight**</b>	1990 lbs.	2150 lbs	2110 lbs.	2270 lbs.	2830 lbs.



# Deck Over Standard Trailer

	817-3.5	817-5.0	920-6.10	920-6.12	920-7.14
<b>Overall Length</b>	21'3"		25' 3 1/2"		
<b>Overall width</b>	96"		101 1/2"		
<b>Deck length w/bvt'1</b>	17'		20'		
<b>Beavertail Length</b>	3'		4'		
<b>Deck width</b>	91 1/2"		96"		
<b>Deck height</b>	29 1/2"	30 1/2"	31"	34"	34"
<b>Axles</b>	2@3500	2@5000	2@6000		2@7000
<b>Suspension</b>	Slipper leaf spring				
<b>Wheels</b>	15" White spoke, 5 bolt	15" Silver mod.6 bolt	16" Silver mod.8 bolt		
<b>Tires</b>	ST205/75D 15	ST225/75D 15	245/75R16	235/85R16	
<b>Brakes</b>	Electric Dexter E-Z Lube Standard on all axles				
<b>Coupler Size</b>	Adjustable 2 5/16 ball hitch or pintle ring				
<b>Drop leg jack</b>	7000 lb.				10,000 lb.
<b>G.V.W.</b>	7000	9999	12,000	14,000	
<b>Decking</b>	2" Treated pine				
<b>Trailer Wgt.*</b>	2170	2205	3035	3150	3350
<b>LED Lights</b>	STANDARD				



## Features:

- Full length rub rail with stake pockets
- Electric brakes on both axles
- Heavy duty 2 5/16" ball or pintle hitch
- Breakaway kit
- Primed & Painted electrostatically with polyurethane paint
- MIG welded reinforced frame
- 2" wide board pressure treated deck
- Modular wiring harness internally grounded
- 7000# top wind drop leg jack
- E-Z Lube axles
- Silver automotive style wheels
- Chain & binder storage

# Deck Over Trailer - DO924TD

	12K	14K	16K
<b>Deck Length</b>	24'	24'	24'
<b>Tilt Length</b>	20'	20'	20'
<b>Overall Length</b>	29'	29'	29'
<b>Deck Width</b>	101"	101"	101"
<b>Deck Height</b>	33"	33"	34-1/2"
<b>Axles, Dexter E-Z Lube</b>	2 @ 6000	7000	8000
<b>Suspension</b>	TORSION		
<b>Wheels</b>	16" Silver Mod 8 Bolt	16" Silver Mod 8 Bolt	17.5 8 Bolt
<b>Tires</b>	LT 245/75R16	LT 235/85R16	215/75R17.5
<b>Brakes</b>	Standard Electric All Axles		
<b>Coupler</b>	5 Position Adj. Coupler or Pintle Ring		Pintle Ring
<b>Drop Leg Jack</b>	10K		
<b>G.V.W.R.</b>	12,000	14,000	16,000
<b>G.A.W.R.</b>	12,000	14,000	16,000
<b>Trailer Weight</b>	4500	4600	4700
<b>Decking</b>	2" Treated Pine		
<b>Tilt Angle</b>	14 Degrees		
<b>Tilt Cylinders</b>	2 2.5 x 16" Double Action		
<b>Wiring</b>	Sealed Modular Wiring Harness		
	FULL LENGTH RUB RAIL AND STAKE POCKETS		
	LED LIGHTS STANDARD		



## OPTIONS:

- Wireless Remote Control
- Type 27 Deep Cycle Battery
- Spare Tire
- Gooseneck

# Gooseneck Standard Trailer

	GN-10	GN-12	GN-14	GN-16
<b>Overall Length</b>	27' 9 1/2"		32' 2"	
<b>Overall width</b>	101 1/2"			
<b>Deck width</b>	96"			
<b>Deck length w/ beavertail</b>	20'		24'	
<b>Beavertail</b>	4'			
<b>Deck height</b>	30 3/4"	32 3/4"	33 1/2"	34 1/2"
<b>Overall Height</b>	73"	74"		75"
<b>Axles</b>	2@6000#	2@7000#		2@8000#
<b>Suspension</b>	Slipper leaf springs			
<b>Wheels</b>	6 Bolt 15"	8 Bolt 16"		8 Bolt 17.5"
<b>Wheels</b>	Silver mod wheels			Gray industrial
<b>Tires</b>	ST225/75/15	LT245/75R16	LT235/85R16	LT215/75R17.6
<b>Load range</b>	D	E	G	H
<b>Tire capacities</b>	2540 lbs.	3450 lbs.	3750 lbs.	4750 lbs.
<b>Coupler size</b>	2 5/16" Ball-vertical adjustable			
<b>Jack</b>	1-12k		2-12k	
<b>G.V.W. Rating</b>	10,000 lb.	12,000 lb.	14,000 lb.	16,000 lb.
<b>Trailer Weight*</b>	3250#	3450#	4550#	4750#
<b>Decking</b>	2" Treated			
<b>LED Lights</b>	Standard			
	* Trailer weights may vary due to wood deck density.			



## Features:

- MIG Welded reinforced frame
- 12,000# Heavy duty drop leg jack
- 2 enclosed toolboxes & 1 open toolbox
- Safety chains
- Breakaway kit
- Main beams & gooseneck constructed of same size steel (I-Beams or Channel)
- D.O.T. Approved - shock mounted lights

# Skid Steer Trailer

	SS1012-10	SS1014-10	SS1016-10	SS1018-10	SS1020-10
<b>Overall Length</b>	18'4"	20'4"	22'4"	24'4"	26'4"
<b>Overall Width</b>	101 1/2"				
<b>Bed Length</b>	12'	14'	16'	18'	20'
<b>Bed Width</b>	82"				
<b>Bed Height</b>	20 1/2"				
<b>Axles</b>	2-4" Drop Axles				
<b>Suspension</b>	Slipper Leave Springs				
<b>Wheels</b>	6 Bolt 15"				
<b>Tires</b>	ST225-75D15 8 Ply				
<b>Coupler Size</b>	2 5/16 Ball or Pintle Ring				
<b>Jack</b>	7000 lb. Drop Leg				
<b>G.V.W.</b>	9990#				
<b>Trailer Weight **</b>	2050	2250	2450	2640	2790
<b>Decking</b>	2" Treated				

	SS1016-12	SS1018-12	SS1020-12	SS1016-14	SS1018-14	SS1020-14
<b>Overall Length</b>	22' 4"	24' 4"	26' 4"	22' 4"	24' 4"	26' 4"
<b>Overall Width</b>	101 1/2"					
<b>Bed Length</b>	16'	18'	20'	16'	18'	20'
<b>Bed Width</b>	82"					
<b>Bed Height</b>	22 1/4"			22 1/2"		
<b>Axles</b>	2-4" Drop Axles					
<b>Suspension</b>	Slipper Leave Springs					
<b>Wheels</b>	8 Bolt 16"					
<b>Tires</b>	LT245/75/R16 Load Range "E"			LT235/85/R16 Load Range "G"		
<b>Coupler Size</b>	2 5/16 Ball or pintle ring					
<b>Jack</b>	7000 lb. Drop Leg			10000 lb. Drop Leg		
<b>G.V.W.</b>	12,000#			14,000#		
<b>Trailer Weight **</b>	2600	2790	2940	2655	2855	2995
<b>Decking</b>	2" Treated					

